

THERMO BUTTON – HYGRO BUTTON



The smallest temperature / humidity logger in the world
**FOR ALL YOUR TEMPERATURE AND HUMIDITY CONTROLS, PRODUCT TRACKING,
 TRANSPORT, STORAGE CONTROLS, HACCP!**

Small, rugged, it can survive any harsh environment, resists to dust, to water.

MAIN FEATURES

- Records date and time
- Programmable low and high alarm thresholds with temporization parameters
- Start delay

PRESENTATION

- Ø 16 mm, 6 mm thick
- Protected in stainless steel can
- Splash-proof: IP 65
- Unique serial number

5 BUTTONS AVAILABLE

	Thermo Button 21G	Thermo Button 22L	Thermo Button 22T	Thermo Button 22E	Hygro Button 23
Temperature range °C	-40 / +85°C	-40 / +85°C	0 / +125°C	+15/+140°C	-20 / +85°C
Humidity range H%	-	-	-	-	0 / 100%
Accuracy	± 1°C	± 0.5°C	± 0.5°C	+110/+140°C: ±1.5°C	± 0.5°C / 5%
Resolution	0.5 °C	0.1 or 0.5°C	0.1 or 0.5°C	0.1 or 0.5°C	0.1 or 0.5°C
Size of memory/readings	2048	4096 or 8192	4096 or 8192	4096 or 8192	4096 or 8192
Sample rate	1 to 255 min	1 sec to 273 h	1 sec to 273 h	1 sec to 273 h	1 sec to 273 h
Battery life span	10 years max		300 hours max		10 years max

3 WAYS TO READ OR PROGRAM YOUR BUTTONS



On your PC



On your Android Smartphone



On the Ethernet

ATTACHMENTS



Color key fobs



Wall mount eyelet



White or custom printed PVC card



Waterproof capsule

Works with THERMOTRACK **PC**, THERMOTRACK-**ONLINE**,
 THERMOTRACK **MOBILE EDITION** and THERMOTRACK-**WEBSERVE**